

DERWENT-ACC-NO: 1996-214884
DERWENT-WEEK: 200045
COPYRIGHT 1999 DERWENT INFORMATION LTD

TITLE: Magneto electric conversion element - in which
protection layer
comprising resin and stress relieving material surrounds
magneto resistance
effect generation layers which are formed on magnetic
substance substrate

PATENT-ASSIGNEE: MURATA MFG CO LTD[MURA]

PRIORITY-DATA: 1994JP-0213756 (September 7, 1994)

PATENT-FAMILY:

PUB-NO	PUB-DATE	LANGUAGE
PAGES	MAIN-IPC	
JP 3085100 B2	September 4, 2000	N/A
005	H01L 043/08	
JP 08078755 A	March 22, 1996	N/A
005	H01L 043/08	

APPLICATION-DATA:

PUB-NO	APPL-DESCRIPTOR	APPL-NO
APPL-DATE		
JP 3085100B2	N/A	1994JP-0213756
September 7, 1994		
JP 3085100B2	Previous Publ.	JP 8078755
N/A		
JP 08078755A	N/A	1994JP-0213756
September 7, 1994		

INT-CL (IPC): G01R033/09; H01L043/08

ABSTRACTED-PUB-NO: JP 08078755A

EASIC-ABSTRACT: The magneto electric conversion element
(10) has a magnetic
substance substrate (1). Above this substrate, multiple
magneto resistance
effect generation layers (2) are formed.

These layers are surrounded by a protection layer (3a)
which consists of a
mixture of resin and stress relieving material. The

magnetic substance
substrate is thus bonded to this protection layer.

ADVANTAGE - Reduces constraint during pattern designing
process.

CHOSEN-DRAWING: Dwg.1/7

TITLE-TERMS:

MAGNETO ELECTRIC CONVERT ELEMENT PROTECT LAYER COMPRISE
RESIN STRESS RELIEVE
MATERIAL SURROUND MAGNETO RESISTANCE EFFECT GENERATE LAYER
FORMING MAGNETIC
SUBSTANCE SUBSTRATE

DERWENT-CLASS: S01 U12

EPI-CODES: S01-E01B; U12-B01B;

SECONDARY-ACC-NO:

Non-CPI Secondary Accession Numbers: N1996-180309

DERWENT-ACC-NO: 1999-085809
DERWENT-WEEK: 199911
COPYRIGHT 1999 DERWENT INFORMATION LTD

TITLE: Silicon radder (sic) type photopolymer composite,
and process for
patterning - for passivation layer for semiconductor appts.

PATENT-ASSIGNEE: MITSUBISHI ELECTRIC CORP[MITQ]

PRIORITY-DATA: 1997JP-0133602 (May 23, 1997)

PATENT-FAMILY:

PUB-NO	PUB-DATE	LANGUAGE
PAGES	MAIN-IPC	
JP 10319597 A	December 4, 1998	N/A
018	G03F 007/075	

APPLICATION-DATA:

PUB-NO	APPL-DESCRIPTOR	APPL-NO
APPL-DATE		
JP10319597A	N/A	1997JP-0133602
May 23, 1997		

INT-CL (IPC): C08F002/48; C08F290/14 ; C08L083/04 ;
G03F007/004 ;
G03F007/028 ; G03F007/075 ; H01L021/312

ABSTRACTED-PUB-NO: JP10319597A

BASIC-ABSTRACT: Claimed silicon radder type photopolymer
composite comprises a
silicon radder resin of the formula (1), and a
photocrosslinking agent or a
photopolymerisation initiator.

Formula (1)-p

R1, R2 = H, aryl, alkyl, unsaturated group;

R3, R4, R5, R6 = H, aryl, alkyl, trialkylsilyl; unsaturated
group; at least 1
wt.% of the total of R1 - R6 is a light-sensitive group; n
= integer).

Also claimed is the patterning process comprising (a)

forming the layer of the composite on a base plate, (b) heating the composite layer at a temperature at least 5 deg. C lower than the m.pt. of any of the component, (c) exposing the layer through a photomask and (d) developing the exposed layer.

Further claimed is the semiconductor apparatus comprising a base plate and the photopolymer layer.

USE - The composite is used for providing the passivation layer for semiconductor apparatus.

ADVANTAGE - The passivation layer has good stability, and is formed by a rapid and simple patterning process.

CHOSEN-DRAWING: Dwg.0/1

TITLE-TERMS:

SILICON TYPE PHOTOPOLYMERISE COMPOSITE PROCESS PATTERN
PASSIVATION LAYER
SEMICONDUCTOR APPARATUS

DEFWENT-CLASS: A26 A89 G06 L03 P84 U11

CFI-CODES: A06-A00E4; A08-C01; A08-D01; A11-C02B; A12-E07C;
A12-L02B2; G06-E02;
G06-F02C; G06-F03D; G06-G17; G06-G18; L04-C06;

EFI-CODES: U11-C05A; U11-C20;

ENHANCED-POLYMER-INDEXING:

Polymer Index [1.1]

Q18 ; D11 D10 D12 D18*R D51*R F81 F83 F86 F87 ; P1445*R
F81 Si 4A
; L9999 L2391 ; L9999 L2073 ; M9999 M2073 ; S9999 S1627
S1605 ;

H0179 ; H0282

Polymer Index [1.2]

Q18 ; ND01 ; ND04 ; B9999 B4988*R B4977 B4740 ; K9847*R
K9790 ;
K9869 K9847 K9790 ; B9999 B5243*R B4740 ; B9999 B5094
B4977 B4740
; B9999 B3532 B3372 ; Q9999 Q8673*R Q8606 ; Q9999 Q7476

Q7330 ;
N9999 N7147 N7034 N7023 ; Q9999 Q7170 Q7158 Q7114 ;
K9585 K9483
Polymer Index [1.3]
018 ; D01 D11 D10 D07 D25 D22 D33 D79 D43 D50 D93 F23 ;
D01 D11
D10 D19 D18 D23 D22 D32 D76 D41 D93 F23 F00 ; A999 A179
A157
Polymer Index [1.4]
018 ; D01 ; R01056 G2595 D01 D11 D10 D50 D63 D86 F41
F89 ; A999
A475

SECONDARY-ACC-NO:

CPI Secondary Accession Numbers: C1999-025938

Non-CPI Secondary Accession Numbers: N1999-062203